JAKSI TAKSI

stageplan

VOCAL RACK (Radek)

- 1x XLR IN (in ear) - 1x XLR OUT (wireless mic)

~ 220V

GUITAR AMP 1x mic

~ 220V

DRUMS

- 1x kick drum1x snare drum
- 1x tom. 1x floor tom
- 1x hihar, 2x overhead

Michal

M4 (in ear) SAMPLER RACK

- 2x XLR BAL OUT (L/R) - in ear 1x XLR IN

~ 220V

BASS AMP DIXLR OUT

Radek: +420 603 362 441

~ 220V



М3

~ 220V

Šimon

V1

Acoustic Guitar

M1 (in ear)

Radek

V2

M2

Tony

Drums:

22" kick, 14" snare 10" tom, 16" floor tom hihat, cymbals

Amps:

Bass: Ampeg stack 250W, 1x15" box Guitar: ESH amp 100W, Marshall 2x12" box

Vocals:

V1: lead vocal - wireless mic V2: backing / lead vocal V3: backing vocal

Sampler:

2x XLR BAL mono out = L/R stereo

Monitors:

M1: in ear monitoring M2: standard monitor M3: standard monitor M4: standard / in-ear

Acoustic Guitar:

6.3mm mono jack UNBAL output

JAKSI TAKSI - MONITORING LIST

INPUT	NAME	TYPE	INPUT	LEVEL
M1	RADEK	IN EAR	XLR	
	- LEAD VOCAL (INPUT 13, RADEK)			100
	- BASS GUITAR (INPUT 11, TONY)			40
M2	TONY	NORMAL		
	- VOCAL (INPUT 14, TONY)			100
	- LEAD VOCAL (INPUT 13)			20
	- KICK DRUM (INPUT 1)			10 ?
	- BASS GUITAR (INPUT 11, TONY)			10 ?
M3	ŠIMON	NORMAL		
	- VOCAL (INPUT 15, ŠIMON)			100
	- LEAD VOCAL (INPUT 13, RADEK)			30
	- VOCAL (INPUT 14, TONY)			30
	- LEAD GUITAR (INPUT 10, ŠIMON)			10 ?
	- LEAD GUITAR (INPUT 10, ŠIMON)			10 ?
M4	MICHAL	NORMAL / IN EAR		
	- BASS GUITAR (INPUT 11,TONY)			30
	- LEAD VOCAL (INPUT 13, RADEK)			10 ?
	- LEAD GUITAR (INPUT 10, ŠIMON)			10 ?
	- KICK DRUM (INPUT 1)			10 ?

JAKSI TAKSI - INPUT LIST

INPUT	TYPE	OUTPUT	MIC	PAN
1	KICK DRUM			
2	SNARE			
3	ТОМ			
4	FLOOR TOM			
5	ні нат			
6	OH-L			
7	OH-R			
8	SAMPLER L	XLR BALANCED		L 100
9	SAMPLER R	XLR BALANCED		R 100
10	LEAD GUITAR (ŠIMON)			
11	BASS GUITAR (TONY)	XLR BALANCED		
12	ACOUSTIC GUITAR (RADEK)	JACK 6.3 UNBAL (NEED DI BOX)		
13	LEAD VOCAL (RADEK)		WIRELESS MIC	
14	VOCAL (TONY)			
15	VOCAL (ŠIMON)			

Notes:

- need wireless vocal hand mic (INPUT 13, RADEK)
- acoustic guitar is variable on some concerts may not appear, in case there is it needs 1x DI-BOX (INPUT 12, acoustic guitar, RADEK)
- drummer choose monitor type depended on situation standard speaker box or in ear
- red lines in monitoring list are necessary to be routed, others are variable